



# Crane Report

## PRACTICAL EXAMINATION—OVERHEAD CRANES

NCCCO has established specific safety conditions and guidelines that each practical exam must follow. This Crane Report is a verification tool used to ensure that all testing parameters are within strict, safe working conditions. Before testing is conducted, the crane being used for testing must have its own unique report filled out. This report should be completed in ink, signed by the Examiner, and sent with the Site Report to: NCCCO—Testing Services Department, 1960 Bayshore Blvd., Dunedin, FL 34698.

Reminder: *Each crane used must have a separate report filled out.*

TEST SITE NUMBER	DATE
NAME OF TEST SITE COORDINATOR	
NAME OF PRACTICAL EXAMINER	
CRANE OWNER/COMPANY NAME	
CRANE OWNER/COMPANY POINT OF CONTACT	PHONE NUMBER

### CRANE TYPE *(Check all boxes that apply to the characteristics of the crane you plan to test on.)*

*Cranes used for CCO Practical Exams must have powered bridge, trolley, and hoist functions.*

- OVERHEAD BRIDGE CRANES:     TOP RUNNING                       UNDERHUNG  
     SINGLE GIRDER                       DOUBLE GIRDER
- 
- GANTRY CRANES:                       GANTRY                       SEMI GANTRY                       CANTILEVER GANTRY
- 
- METHODS OF OPERATION:     PENDANT CONTROL     CAB OPERATED\*     REMOTE CONTROL
- 
- TYPES OF CONTROLS:                       VARIABLE FREQUENCY DRIVE                       MAGNETIC CONTROL

\*FOR CAB-OPERATED CRANES, PLEASE LIST THE HEIGHT OF THE CAB FLOOR: \_\_\_\_\_

### CRANE DESCRIPTION *(Provide data for items 1 thru 6 using the manufacturer's operating manual.)*

1. MAKE/MODEL	2. SERIAL NUMBER	3. MAX RATED CAPACITY (MINIMUM 3 TONS REQUIRED)
4. CONFIGURATION OF CRANE (ROPE SIZE AND TYPE, ANCILLARY EQUIPMENT, ETC.)		

*Please complete items 5 and 6:*

5. BRIDGE LENGTH (25 FT. MIN. REQUIRED): \_\_\_\_\_ FT.  
 6. LOAD HOOK HEIGHT (13 FT. MIN. REQUIRED): \_\_\_\_\_ FT.

*The following are the overhead crane Test Weight specifications:*

7. TEST WEIGHT: \_\_\_\_\_ LB. (1,500–2,000 LB. REQUIRED)

NOTE: FOR CAB-OPERATED CRANES WITH A CAB FLOOR MORE THAN 25 FT. ABOVE GROUND, THE TEST WEIGHT MUST HAVE FOUR PERIMETER CHAINS IN ADDITION TO THE CENTER CHAIN.

***I attest that this is a true and accurate report of the crane and Test Weight being used for testing.***

EXAMINER SIGNATURE	PRINTED NAME OF EXAMINER	EXAMINER'S ACCREDITATION #	DATE
--------------------	--------------------------	----------------------------	------